

PureWaterMachine™

by VERTEX

Produces More Clean Water

75-GPD Reverse Osmosis Membrane cleans water faster

Benefits

- Great tasting water from your tap
- Takes out chlorine taste and odors, dirt and sediment
- Won't scale humidifiers, steam irons or coffee pots
- No need to buy bottled water - better for the environment
- Comes ready to install, with manual

Standard Features

- 3 filter canisters
- High-capacity post filter in third canister
- 75-GPD encapsulated membrane
- All quick connect fittings
- 3/8" tubing to tank and faucet
- 1 year limited warranty



Use the **VERTEX 3C-4.0** to make *more* clean, great tasting water from your tap with its 75 GPD RO membrane. It eliminates the unwanted contaminants from the water used for drinking and cooking in the home. The heart of the system is the reverse osmosis membrane that removes an average of 95% of the dissolved solids in your water.

This system has 3-filter canisters for easier and faster filter replacement. The post filter is a longer lasting, larger capacity coconut shell activated carbon replaceable filter. The 75 GPD membrane is in an encapsulated housing for easier replacement. The 3/8" tubing provides 50% more water flow at the faucet. All fittings are quick-connect for ease of assembly. Comes complete with connection hardware, faucet, tubing and instruction manual.

STAGE ONE

Sediment Filter, 5-Micron Polyspun Cartridge, 2 1/2" dia. x 9 3/4" long

STAGE TWO

Activated Carbon Block Filter 5 Micron, 2 1/2" dia. x 9 3/4" long

STAGE THREE

Reverse Osmosis Membrane, Osmonics 75 GPD TFC @ 65 PSI Pressure Differential

STAGE FOUR

Post-Filter, Granular Activated Carbon, 2.5" dia. x 9.75" long cartridge

TANK

4.0 Gallon Plastic Tank (metal tank available), Pre-pressurized with Butyl Bladder (2.5 gal. water capacity when full)

Specifications: Shipping Weight: 26 lb. Dimension: 15" L x 6" W x 15.5" H, Tank: 11 dia. x 15.5" H

Conditions of Use: Water must be microbiologically safe; System pressure, 40 min to 100 max psi; Temperature, 40 to 100° F; PH Range, 3 to 10; Turbidity – less than 1.0 NTU; TDS, 1500 PPM max

ORDERING INFORMATION

4 stage 75 GPD Reverse Osmosis	3C-4.0
Air Gap Faucet option	add /AG
Self-piercing Saddle Valve option	add /SV
Booster Pump option	add /P
Filter Replacement Kit	FK-102

Authorized Dealer

